

Application
for
United States Letters Patent

To all whom it may concern:

Be it known that We,

Markus ANDREASSON and Per ASTRAND

have invented certain new and useful improvements in

METHOD AND DEVICE FOR RECORDING OF INFORMATION

of which the following is a full, clear and exact description:

1054264-1-1301

METHOD AND DEVICE FOR RECORDING OF INFORMATION

5

TECHNICAL FIELD OF THE INVENTION

The present invention relates to a method and a device for recording of text by imaging the text on an optical sensor in a handheld device, said sensor being intended for digital recording of images.

BACKGROUND OF THE INVENTION

It is sometimes desired to abstract parts of text or image information in a document which may later be edited using appropriate software in a computer. A known method of inputting text and image information into a computer is to use a stationary or portable scanner.

A stationary scanner is suitable for entering entire pages with text and image information, the scanner being automatically passed across the page at a constant speed. This type of scanner is not suited for inputting selected parts of information on a page.

A portable, handheld scanner may be used any time interesting information is to be scanned, but normally has a limited field of view.

US-5,301,243 discloses a hand-held scanner for reading characters from a string of characters on a substrate. The scanner is moved in contact with the substrate along the character line and has an optical system which images a small part of the substrate. The optical system comprises a CCD type line sensor provided with a plurality of light-sensitive elements arranged in a line. When the scanner is passed across the characters on the substrate, a succession of vertical slices of the characters and of the spaces between them is recorded. The slices are stored in the scanner as a digital bit-map image. OCR software (OCR = Optical Character Recognition)

is then used to identify the characters and store them in character-coded form, such as ASCII code. The character recognition can be made either in the scanner or in an external computer to which the bit-map image is sent.

5 Another type of hand-held scanner for inputting text is disclosed in US-4,949,391. This scanner has a two-dimensional sensor which records images of the underlying surface as the scanner is being moved across the same. The scanner is restricted to movements in a direction
10 which is determined by a wheel in contact with the surface. Before the recorded images are assembled into a composite image, redundant information is removed from the images. The composite image can be analyzed in a computer for identification of characters.

15 A drawback with the handheld scanners described above is that their field of view is relatively small. In order to record a large amount of information, such as passages consisting of several lines, a user must therefore move the scanner back and forth across the
20 surface repeatedly. Moreover, the movement has to follow a predetermined path, such as along the lines of text.

Publication WO 99/57678 discloses a device for recording information from a substrate. The device may operate in two modes, one scanner mode, in which lines of
25 text is scanned, and a photograph mode, in which separate pictures are taken of a document or an object.

Publication WO 98/20446 discloses a scanner pen, which is adapted to be moved over a line of text for scanning the text. As the pen moves over the text image,
30 several pictures are taken of the text. The pictures are processed by a computer and assembled or stitched together for forming a composite image of the entire line of text, which cannot be read by a single picture. The scanner pen can only scan a single line of text at each
35 time.

Thus, there is a need for a handheld scanner pen of the above-mentioned type which is adapted to scan several

0054284-1301
TOE T-1301

lines of text simultaneously as well as smaller pictures.

SUMMARY OF THE INVENTION

An object of the present invention is to provide
5 a scanner pen which enable fast recording of text in real time.

Another object of the invention is to provide a
scanner pen which may be used at a distance from the text
and may scan several lines of text in a single stroke as
10 well as discrete pictures.

These objects are obtained by a method and a device
for recording information by imaging on a light-sensitive
sensor for obtaining at least two images of the
information having partially overlapping contents. The
15 method comprises converting the information in each of
the images to a coded representation, comparing the coded
representation of said images for determining an overlap
position, and assembling the images to form a composite
image. The coded representation may be a character code,
20 such as ASCII. Alternatively, the coded representation
may comprise a division of the information inside
boarders, such as rectangles, each comprising portions of
the information, such as words included in said
information. Thereafter, the composite image may be
25 converted to a character code format, such as ASCII-code.
Alternatively, each image may be separately converted into
character code format, such as ASCII, before assembling.

The method may further comprise determining
structures in each of said images, such as direction of
30 lines or text line directions in each image. This may be
accomplished by means of a Hough transformation of each
image. This information may be used for adjusting the
rotational position and/or perspective of each image in
dependence of the direction of lines. The information may
35 also be used for the division of the image in
reactangles.

A concept of the present invention is to record a

plurality of images of a text, said images overlapping each other, each image comprising several lines of text. Subsequently, OCR (Optical Character Recognition) is carried out as regards the recorded images, resulting in sets of characters. The sets of characters may contain a number of characters indicating "end of line" if the text comprises several lines. Then the sets of characters are assembled using the characters in the sets of characters. An advantage of this mode of operation is that relatively large images can be recorded at a time, without the assembling of the images being cumbersome since the images are converted into character codes before being assembled. The effective resolution is small in a set of characters compared to a bit-map image, thus saving computing power. The effective resolution in the set of characters is a single character. Thus, assembling in two dimensions may be possible with the present invention in a handheld device.

The lines of text in two subsequent images do not necessarily coincide in the vertical direction. The first line in a first recorded image may correspond to the second line in a second recorded image. However, the assembling will adjust the vertical position so that correct assembling is obtained.

By a set of characters is meant a plurality of characters, from which the relative positions of the characters can be determined. The set of characters may be a string of characters comprising characters for blank and end of line.

A device for recording a text images the text on a light-sensitive sensor with a two-dimensional sensor surface, which sensor is intended for digital recording of images of the text, said images having partly overlapping contents. The device is characterized in that it is adapted to convert at least two of the images recorded by the sensor into a set of characters each, comprising a plurality of characters, by means of

character recognition. The device is adapted to subsequently assemble the sets of characters with the aid of the characters in the sets of characters.

By carrying out character recognition before assembling the images, the operation of assembling large images at pixel level can be omitted. Moreover, there is less risk that a character would not be recognized owing to poor assembling, which may be the case when digital images are assembled in pixel level and then character recognition is carried out in an area that is overlapped by both images that are assembled. Then, the character may be distorted if the assembling is not carried out properly, which may results in that the character is not recognized in the character recognition process.

According to this invention, the character recognition process take advantage of the original quality of the image for character recognition. By first converting the images into sets of characters, the actual assembling of the sets of characters may be quick since the number of characters is considerably smaller than the number of pixels in the recorded images.

Moreover, by OCR interpretation of each image before the assembly thereof, a plurality of OCR interpretations of the same character will be obtained, one for each image where the character is included, and the interpretation which gives highest recognition probability can be selected.

Alternatively, it is possible to assemble the sets of characters using words in the set of characters. Thus, entire words in one of the sets of characters that are to be assembled are compared with words in the other of the sets of characters that are to be assembled. When assembling words, it may be required to compare each individual character.

By word is meant a plurality of characters which also includes special characters. The special characters are, for example, blank, full stop, comma or end of line.

The method may comprise finding the lines of text in the recorded images, to find start and end of words along the lines of text and to select which of the recorded images are to be converted into sets of characters with the aid of the identified start and end of the words in the recorded images, so that only images with the necessary information are converted into sets of characters or that images with duplicate information may be discarded. By identifying start and end of the words along the lines of text, it will be possible to make a rough assembling of the images without first making optical character recognition. When the start and end of the words have been identified, the recorded images are corrected as regards rotation and perspective. By making a rough assembling of the images, it will be possible to find out how the images overlap each other. The images which contain only information that is available completely in other images then need not be converted into sets of characters.

Start and end of words along the lines of text may be identified by searching, in each pixel along a line through the lines of text, for the number of dark pixels a predetermined number of pixels up and down from the line of text. An end of a word being defined as if there are no dark pixels in a predetermined number of pixels above and below the line of text, i.e. there are blanks. To manage italics one may alternatively search along an oblique line. It is, of course, possible to search for white pixels, instead of dark pixels, if the text should be brighter than the background, i.e. inverted.

The images may be converted into binary images, i.e. images containing merely black and white, since this facilitates the continued image processing.

Moreover, the method may comprise finding the lines of text in the recorded images using the Hough transformation of the recorded images. The Hough transformation can briefly be described as follows. There

is an infinite number of straight lines extending through a point in an XY plane. The equation of the straight line for each of these lines can be expressed with two parameters. If the parameters of the individual lines are plotted in a diagram, a curve is obtained which corresponds to the Hough transform of the point. In this way, it is possible to plot curves for any of the points in the XY plane. The Hough transform of two different points will intersect in a point, which corresponds to the equation of the straight line extending through the two points. If the Hough transforms for all the dark pixels in a recorded image are plotted, a large number of intersections between the different Hough transforms will be obtained. However, there is a maximum number of intersections for lines following the lines of text.

The device may comprise a memory adapted to store the recorded images, which are to be converted into sets of characters, in the memory, and to convert the stored images into sets of characters after completion of the recording of the images. By only storing the recorded images which are to be converted into sets of characters, the memory space which is required for storing recorded images is minimized. By converting the stored images into sets of characters after the recording of images has been completed, it is not necessary to place high demands on the speed of the optical character recognition, which would be the case if it were to be carried out while images are being recorded.

The device is advantageously designed in such a manner that a user can hold it by hand and at a distance from a substrate to record text on the substrate.

The device may be adapted to correct the images for rotation before they are converted into sets of characters. In the case where the lines of text in the recorded images have been identified, the correction for rotation can be carried out in a relatively simple way. However, some optical character recognition programs can

process also rotated images, in which case the rotation is not required.

Correspondingly, the device may correct the images for perspective before they are converted into sets of characters since the optical character recognition may be facilitated if all letters have the same size in the images.

The device may be designed as a reading head which is connected to a calculating unit in which the recorded images are processed.

The device may be adapted to assemble the sets of characters by comparing the sets of characters in pairs, the sets of characters being compared in a number of relative positions displaced relative to each other. Thus, a first character in a first set of characters is compared with characters in the second set of characters until correspondence is achieved or until the first character in the first set of characters has been compared with all characters in the second set of characters. Subsequently, the correspondence of the second characters in the first set of characters is compared with the characters in the second set of characters. By making the comparison for a large number of different relative positions, a plurality of total numbers of points can be obtained, the total number of points reflecting the correspondence between the two sets of characters for the specific position. In this way, an optimum relative position can be obtained.

The device may be adapted to store the recorded images that are to be converted into sets of characters along with a serial number indicating in which order the images have been recorded, and to assemble the sets of characters with the aid of the serial number for the images corresponding to the sets of characters. Especially in the case where first all images are recorded and not until then the character recognition and the assembling are begun, the serial numbers may be used for

the recorded images since then a large number of images are to be assembled.

According to a second aspect of the present invention, a method is provided for recording of text on a substrate, comprising the step of imaging and digitally recording images of the text, the images having partly overlapping contents. The method is characterized in that it comprises the steps of converting at least two of the recorded images into a set of characters, each with a plurality of characters, by means of optical character recognition, and putting together the sets of characters with the aid of the characters in the sets of characters.

The area recorded by the sensor may be arranged so that a plurality of lines of text are imaged in a recorded image.

According to a third aspect of the present invention, a computer-readable storage medium, in which a computer program is stored which is adapted to be used for conversion of digital images, which are recorded by an image sensor, into text. The storage medium is characterized in that the computer program comprises instructions for making the computer receive digital images as input signals, convert the digital images into sets of characters, with a plurality of characters, by means of character recognition, and put together the sets of characters with the aid of the characters in the sets of characters.

Further objects, features and advantages of the invention will appear from the following detailed description of embodiments of the invention with reference to the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic view of a device according to a first embodiment of the present invention.

Fig. 2 is a schematic block diagram of parts of the embodiment of Fig 1.

Fig. 3 is a schematic view of images of text on a sheet of paper, which are recorded according to the invention.

5 Figs. 4a and 4b are diagrams, illustrating the principle of the Hough transformation.

Fig. 5 is a diagram, which shows maximum points for the Hough transform of two different images.

Fig. 6 is a diagram and a histogram for illustrating the detection of start and end points of words.

10 Figs. 7a and 7b are diagrams for illustrating the division of the text images into words.

Fig. 8 is a diagram of two images converted to characters for assembling.

15 Fig. 9 is a diagram for illustrating lines of text in a recorded image.

Fig. 10 is a flow chart of the operation of a computer program according to the invention.

20 Fig. 11a, 11b and 11c are shematic representations of a text, division thereof in rectangles and display on a small display.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

Fig. 1 discloses a scanner pen, comprises a casing 1 having approximately the same shape as a conventional
25 highlighter. In one short side of the casing there is an opening 2, which is intended to be directed at an area on a substrate which a user wants to image. The information carrier can be a sheet of paper.

The casing 1 essentially contains an optics part 3,
30 an electronic circuitry part 4 and a power supply part 5.

The optics part 3 comprises a lens system 7, light-emitting diodes 6, and an optical sensor 8 constituting an interface with the electronic circuitry part 4. The light-emitting diodes 6 may be used to increase the
35 illumination.

The light-sensitive optical sensor 8 may be a two-dimensional CMOS unit or CCD unit (CCD = Charge Coupled

Device) with a built-in AD converter. Such sensors are commercially available. The sensor 8 may be mounted on a printed circuit board 11.

The power supply to the device is obtained from a battery 12 which is mounted in a separate compartment 13 in the casing.

Fig. 2 is a block schema of the electronic circuitry part 4, which comprises a processor 20 which, via a bus 21, is connected to a read-only memory ROM 22, in which the program of the processor is stored, to a write/read memory RAM 23, which is the work memory of the processor and in which the images from the sensor as well as characters that are interpreted from the recorded images are stored, to a control logic unit 24 and to the sensor 8.

The control logic unit 24 is connected to a number of peripherals, such as a display 25 mounted in the casing, an IR transceiver or short-range radio link 26 for transferring information to/from an external computer, buttons 27 by means of which the user can control the device, and an operation indicating device 28 consisting of a second set of light-emitting diodes which may indicate whether recording occurs or not and other operating conditions. The control logic unit 24 generates control signals to the memories, the sensor and the peripherals. The control logic unit also manages the generation and the prioritization of interrupts to the processor. The buttons 27, the transceiver 26, the display 25 and the light-emitting diodes 6 are controlled by the processor by writing and reading in the records of the control logic unit. The buttons 27 generate interrupts to the processor 20 when activated.

The function of the device will now be described. A sheet of paper 9 is provided with a plurality of lines of printed text 10 as shown in Fig. 3. When a user activates the scanner pen by means of the buttons 27 and passes it across the sheet of paper with the opening 2 directed

towards the sheet of paper, three images 14, 15, 16 are recorded. Each of the images 14, 15, 16 is exposed to OCR processing and the text of the images is converted into sets of characters as illustrated in Fig. 8. Subsequently the sets of characters are assembled or stitched so as to form a complete text. As shown in Fig. 3, the images 14, 15, 16 may be rotated in relation to each other. Thus, a first image 14 is turned or rotated in relation to a second image 15, which in turn is rotated in relation to a third image 16.

In order to optimize the optical character recognition in the recorded images 14, 15, 16 it is advantageous to know the orientation of the lines of text in the image. Therefore, the orientation of the lines of text is detected before the character recognition is carried out.

The detection of the orientation of the lines of text may be carried out using the Hough transformation.

Referring to Figs 4 and 5, the Hough transformation will now be generally described. Fig. 4a shows five points in a plane with the coordinate axes X and Y. Fig 4b shows the Hough transform of the five points in Fig. 4a. A first point 18a has a first Hough transform curve 19a which describes all the straight lines extending through the first point 18a in Fig. 4a as a function of the parameters θ and ρ where θ is the angle of the straight lines through the point and ρ is the distance of the straight lines from origin. The Hough transform curves have a sinusoidal shape. Correspondingly, the second 18b, third 18c, fourth 18d and fifth 18e points have a second 19b, third 19c, fourth 19d and fifth 19e Hough transform curve. The second 19b, third 19c and fourth 19d Hough transform curves in Fig. 4b intersect in a point. This point in Fig. 4b corresponds to a straight line in Fig. 4a extending through both the second point 18b and the third point 18c and the fourth point 18d.

Fig. 9 shows the second recorded image 15 from Fig. 3, which consists of a plurality of pixels in which

lines of text are to be found. For each black pixel in the second recorded image 15, a Hough transform curve is calculated. The Hough transforms are inserted in one and the same diagram.

5 Fig. 9 shows a first line 32 and a second line 33. Lines having approximately the same direction as the first line 32 will intersect a larger number of points than lines having approximately the same inclination as the second line 33 since the dark pixels in the recorded
10 image 15 are positioned along lines of text having approximately the same direction as the first line 32.

Fig. 5 illustrates that the maximum number of intersections can be used to determine the orientation of the lines of text. The circles 73 correspond to points
15 in the Hough transform diagram where several Hough transform curves of points in Fig. 9 intersect, i.e. maximum of intersections. The circles 73 corresponds to the image 15 and are positioned along a straight line 34. From the distance between the circles 73, the distance
20 between the lines of text can be determined. The position of the intersecting line 34 along the θ axis indicates the rotation of the recorded image. The second line 35 in Fig. 5 corresponds to the image 14 and extends through a plurality of maximum indicated by crosses 36 in the
25 diagram. The inclination of the second line 35 indicates that the image has a perspective, i.e. the lines of text have different rotations. Also the slighth different distances between the crosses 36 indicate that the image has a perspective with larger distances between the lines
30 at the lower portion of the line 36. The displacement of the second intersecting line 35 in relation to the first line along the θ axis indicates that the lines of text are rotated in the recorded image. By means of this information, the image may be adjusted for perspective
35 and rotated, for example to the horizontal direction, which is the same direction as image 15. As appears, image 15 corresponding to line 34 need no adjustment,

while image 14 corresponding to line 35 needs adjustment of the perspective to make line 36 vertical and with approximately equidistant crosses 36 and adjustment as to the rotational position, to move line 35 to the same angle θ as image 15, which may correspond to zero angle.

After identification of the lines of text, an identification of the start and end parts of the words in the recorded image is carried out. Fig. 6 indicates how the letter "e" 37 is detected. As shown in Fig. 6, the number of dark pixels 7 are counted in the vertical direction perpendicular to the line 38, which may be calculated as described above. The number of dark pixels is zero up to the start 39 of the letter "e" and will again be zero at the end 40 of the letter "e". When the number of dark pixels has been zero for a predetermined period, this is detected as the end of a word.

With reference to Fig. 7, the words are indicated as rectangles, the start 41 of the rectangles indicating the start of a word and the end 42 of the rectangles indicating the end of a word. Fig. 7a corresponds to a first recorded image 14 and Fig. 7b corresponds to a second recorded image 15. A length of a first word 43 in Fig. 7a has correspondence in a length of a second word 44 in Fig. 7b. Correspondingly, a length of a third word 45 in Fig. 7a has correspondence in a length of a fourth word 46 in Fig. 7b. By matching the two images, it is possible to find out how the recorded images overlap each other, by only using the graphical information of the length of each word.

Thus, by using the length of the words for each line, it is possible to carry out a rough putting-together or stitching or assembling of the two images. The images are roughly assembled so that a sequence of word lengths in the first recorded image corresponds to a sequence of word lengths in the second recorded image. The word lengths along different lines in the first recorded image should thus correspond to word lengths

along corresponding lines in the second recorded image. In this way, it is possible to determine how the images are displaced relative to each other.

Fig. 3 shows how this may be used to sort out unnecessary images so that optical character recognition need not be carried out as regards all images that are recorded. A first image 47 and a second image 49 completely overlap the area which is covered by a third recorded image 48 which is indicated by dashed lines. By using the method as described in connection with Fig. 7, the third recorded image 48 can be completely omitted, without optical character recognition being carried out. Of course, Fig. 3 is only schematic, since the images often overlap each other to a much larger extent. Indeed, if the scanner pen is held approximately still, all images overlap more or less, and a substantial saving of computing power may be obtained by omitting images with duplicate information. On the other hand, during normal scanning operation, a partial overlap may be used for sorting out errors in the optical character recognition process or the assembling process, in which case overlapping images are not omitted or discarded.

Another method of assembling the images is disclosed in Fig. 8, which shows a first set of characters 50 with a plurality of characters 60 corresponding to the first recorded image 47 in Fig. 3 and a second set of characters 51 with a plurality of characters 61 corresponding to the second recorded image 49 in Fig. 3. The text in the first set of characters and the second set of characters follows the direction of the lines of text 62, which may have been obtained by the Hough transform process described above. The first set of characters 50 and the second set of characters 51 are put together or assembled by comparing characters in the two sets of characters. Firstly, the first character 52 in the first set of characters is compared with each of the characters in the second set of characters 51. The operation

proceeds correspondingly for the second character 63 and the third character 64 in the first set of characters 50. Good correspondence is obtained when the characters in the word "skilled" 53 in the second line of the first set of characters is compared with the word "skilled" 54 in the first line in the second set of characters 51. Since a word can appear in many positions in a text, one starts from the first correspondence found and then compares the rest of the text for this position, a total number of points being obtained which indicates how well the two sets of characters correspond for this position. Subsequently this step is repeated for the next position where correspondence is obtained. Finally, the position is selected in which the total number of points indicates the best correspondence. In Fig. 8, the text is in English but a person skilled in the art understands that the text could just as well be in any other language and that the text in Fig. 8 is only used to illustrate the function of the device. The image may also comprise symbols, such as mathematical expressions, or even line art, to a limited extent.

The two assembling methods may be combined, so that the images are first compared in a rough manner and then on character level. In this way, it will be possible to carry out assembling in two dimensions with limited computing power. If the reading device is first moved to the right like in Fig. 3 and then down and to the left, a larger surface is obtained which is to be assembled in two dimensions. By determining the mutual relationship of the partial images by rough assembling and then on character level, it is relatively easy to obtain both horizontal and vertical assembling. The characteristic that the lines determine the vertical position with great accuracy results in the possibility of alignment.

Each assembling method may alternatively be used separately. If the method using length of words is used separately, the images may be assembled into a composite

image before final conversion of the images to characters by optical character recognition. This method may be used when the images comprises other matter than text, such as small pictures or symbols. In this case, the symbols or
5 small pictures will be handled as if they were words and be included in a rectangle. The assembling process will work, provided that the pictures or symbols are sufficiently small. However, the OCR process will fail to recognize the rectangle as characters, and then the pixel
10 representation may be used instead. Other types of boarders may be used than rectangles, such as an area delimited by more than four straight lines or even curved lines.

If the assembling is carried out after the
15 conversion of each image to character code such as ASCII, small pictures and symbols may be handled separately, at least if they are surrounded by text matter in each image.

As appears from Fig. 7, the images may be processes
20 by division of the image in boarders, such as rectangles. Each rectangle comprises a complete word or a symbol or a picture surrounded by white areas. Several pictures are compared for finding a succession of rectangles which corresponds to the wanted text. When overlapping
25 positions have been determined, each rectangle is given a succession number, comprising the line number and the word number on that line. Thus, in Figs. 7a and 7B, the word 41 obtains designation 1:1, the next word 1:2, and the following word 1:3. On the second line, the first
30 work obtains the designation 2:1, the second word 2:2, the third word 2:3 and the fourth word 2:4. Correspondingly, on the third line, the first word obtains designation 3:1, the second word 3:2, the third word 3:3 and the fourth word 3:4. It is now recognized
35 that the fourth word on the second row, 2:4 corresponds to the second word on line 2 of Fig. 7b, which means that the first word at the second line of Fig. 7b obtains

designation 2:3, the second word 2:4 (corresponding to the fourth word of line 2 of Fig. 7a), the third word 2:5 and the fourth word 2:6. The same goes for the third line of Fig. 7b, in which the first word obtains designation
5 3:3, the second word 3:4, the third word 3:5 and the fourth word 3:6. The words are then arranged in a row of words forming a complete line.

It can now be seen that several words are duplicated in the two pictures, namely word 2:4 and word 3:4. There
10 are further words which are duplicated on the other lines. These duplications may be omitted and replaced by a single word. Else the duplications may be kept and used for increasing the OCR interpretation accuracy.

Finally, the words are OCR processed in the right
15 order to obtain the desired text.

If any rectangle is larger in the vertical direction than a single line, it may obtain designation like 2,3:6, if it occupies lines two and three. In this way, larger objects such as pictures or symbols may be handled.

There are a number of cases in which partial words are included in Fig. 7a but included in full in Fig. 7b, such as word 1:3. In this case, the longest version of the word is used for interpretation. If there is a doubt if this is correct, all fragments may be used to recreate
20 the complete word.

In this way, the images are assembled on a word basis starting from the pixel representation and dividing the image inside borders, such as rectangles which are compared for the best overlapping position. Then,
30 duplicate information is omitted or used for further accuracy and then the words are arranged in the right order and finally converted to ASCII-code.

Pictures or symbols which may not be recognised by the OCR program, may be maintained in pixel format and
35 displayed as such in the final picture. For increased safety, also at least one version of the words may be kept in pixel format in parallel with the OCR-version,

especially if the OCR program indicates a poor quality of processing.

Every new image is compared with previous information in order to find out its orientation therein. Thus, each image is processed both in the vertical direction as well as in the horizontal direction, both forwards and backwards. Thus, it is possible to scan in two dimensions by the present invention. This is possible because of the division of the image in a coded representation which is less time consuming to process, either in the form of rectangles or similar or in the form of ASCII code.

It may be of interest to have some kind of feed-back that the desired information is gathered. This may be accomplished by displaying the assembled information at the screen. However, since the display at a handheld device is rather small, another method would be to display the lines as a succession of pixels at the display, in which one pixel approximately corresponds to a single character. Then, the characters will form words and the layout of words would give a visual indication of the scanned surface. If the processing comprises division into rectangles, these rectangles may be indicated as they are assembled.

Figs 11a, 11b and 11c show how this may be accomplished. Fig. 11a is a text that is to be scanned. Fig. 11b is the division of this text in rectangles. Finally, Fig. 11c is the representation of the rectangles at a small display, in which rectangles are indicated in black pixels and spaces between the rectangles as gray pixels. From Fig. 11c it can be seen that some information is missing as indicated by white pixels 29. The user then directs his scanner pen towards the area missing until the display indicates that all areas are fully covered by at least one image. Finally, the complete image is converted to ASCII, if that has not been done earlier in the process.

If the assembling is done by using the coded representation in the nature of ASCII code, each decoded character is displayed as a black dot on the display screen, while spaces are displayed as grey dots. Any white dot will indicate that information is missing, as described above.

According to the present invention, it is required that the information at least partially is positioned along identifiable lines. If the device is passed across a photograph or some other surface which is not divided into lines, this can easily be recorded by the processor in the device, and this part of the image may be discarded or stored separately as an picture or photograph. If said surface is completely or at least partially surrounded by lines, it would be possible to handle the situation via the invention, as soon as at least a portion of a line is included in every image.

Fig. 10 is a flow chart of the operation of a computer program according to the invention. The computer program is adapted to be executed in the electronic circuitry part 4 of the device. In a first step 55, digital images are received from the sensor 8. In a second step 56, the digital images are converted into strings of characters using character recognition. In a third step 57, the strings of characters are assembled or put together.

It is not necessary to carry out the rough putting-together of the recorded images as described in connection with Fig. 7, and optical character recognition can be carried out directly as regards the recorded images. Moreover, the orientation of the lines of text need not be identified in the recorded images if an optical character recognition algorithm is used which is able to identify characters also when the lines of text are rotated.

A person skilled in the art realizes that the invention is not limited to the embodiments shown and that

many modifications are feasible within the scope of the invention. The invention is only limited by the appended patent claims.

2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2